2-Port Hot Stab
ISO Type 2

Category: Hot Stabs & Fluid Injection Equipment

The 2-Port ISO Type 2 Hot Stab enables secure connections between ROVs, ROV tooling and subsea equipment.

Designed to meet ISO 13628-8 and API 17H requirements, the hot stab is available in 345-bar (5,000 psi) and 690-bar (10,000 psi, shown below) pressure-rated variants.

The hot stab is supplied with a standard flex handle rated to 5 kN axial load and 60 Nm torque.

Type 1 and ZeroLeak options are also available, see: NSS-661 and NSS-662.



Visit our website

Features

- Compatible with ISO 13628-8 API 17H 2-port Type 2 receptacles
- Flexible handle
- 7/16" JIC Ports

Specifications

Male Dimensions (mm)	Ø34/42 (Nose) x 600 (L) x 153 (W) x 70 (H)
Female Dimensions (mm)	Ø76 (OD) x 203 (L)
Male Weight in Air	5.5 kg
Male Weight in Seawater	4.5 kg
Female Weight in Air	4 kg
Female Weight in Seawater	3.5 kg
Pressure Rating	345 - 690 bar (5,000 - 10,000 psi)
Depth Rating	Unlimited

tmt solves tmtrov.com
1 Ambitious Link, Bibra Lake WA 6163
T +61 8 9411 6500 | E sales@tmtrov.com

TMT-NSS-012 Rev 7 PN: M: 0000-0313, F: 0005-4019, H: 0010-6872
Copyright © 2026. All rights reserved. Specifications subject to change without notice.